

# Sunpak RD2000 digital flash



## Highlights

---

The new Sunpak RD2000 flash is a lightweight, compact and full featured digital SLR flash for digital and film cameras. Compatible with the latest Canon E-TTL II, Nikon i-TTL and Sony ADI TTL Digital SLR cameras and has many advanced features. Such as easy to use controls, articulated hot shoe, wide angle panel and EV adjustments. With a high guide number of 65 (ISO 100/feet), the RD2000 can provide superior illumination in any situation. With seamless integration with the latest offerings DSLR cameras, there is no reason to look any further for a flash that is more capable.

## Features

---

- High guide number of 65.6 (ISO 100/feet)
- 180 degree swivel control panel and hot shoe assembly for complete self-contained storage
- Only 3.5" deep and less than 7 ounces
- Bounce head with five settings
- Self-storing flip-down diffuser panel for wide angle lenses
- Five EV adjustments in one half stops
- Runs on 2 AA Alkaline or Ni-MH batteries which keep it small and compact
- Up to 200 flashes at full power with alkaline batteries
- Up to 280 flashes at full power with nickel metal hydride batteries
- Auto power off feature to keep batteries from going dead

## Specifications

---

- Guide number: 65.6 (ISO 100/feet)
- Compatibility: Canon E-TTL-II or Nikon i-TTL
- Design: 180 degree swivel control panel hot shoe (for self-contained storage)
- Flash head: Bounce head with detent settings (vertical to 90 degrees)
- Diffuser: Wide angle, self-storing flip-down diffuser panel
- EV settings: Five settings in one half stops (-1, -0.5, 0, +0.5, +1.0)
- Recycle time: Full output: Alkaline approx. 5 seconds, Ni-MH approx. 4 seconds
- Number of flashes: Full output: Alkaline approx. 200, Ni-MH approx. 280
- Auto effective range: TTL Auto 1.5-10m (f/stop 2)
- Angle of coverage: 24mm or longer (APS-C), 35mm or longer (converted to 35mm film format)
- Wide angle panel: 16mm (APS-C), 24mm (converted to 35mm film format)
- Flash duration: Approx. 1/2,000 – 1/30,000 second
- Power: 2 AA Alkaline or Ni-MH batteries
- Display: LED
- Dimensions: 1.7 high x 2.36 wide x 3.46" deep
- Weight: Approx. 7 ounces (without batteries)

## Catalog Number

---

RD2000C (Canon E-TTL II)  
RD2000N (Nikon i-TTL)

**SUNPAK**<sup>®</sup>

ToCAD America Inc.

53 Green Pond Road

Rockaway, NJ 08766, USA

tocad.com